

Standalone Smoke Detector



Airlight Standalone Smoke detector consumes ultra low current, in case of smoke detection built in sounder produces dual tone 70 db alarm. Built in test switch provided to test the smoke detector

Airlight is one of the most preferred brand fire detectors in the market. Airlight Products Packages are developed in consultation with architects with their choice to suit the interior. We are ISO 9001:2000 certified company, further we practice design & process FMEA (Potential Failure Mode Effective Analysis) to achieve zero defect with highest quality.

CE
EN-54
as per
IS : 11360:85

ISO 9001:2000
ICVQA
REGISTERED QUALITY SYSTEM



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|-------------------------|
| Model | ALSSD - Series |
| Operating Voltage | 6 to 9VDC |
| Maximum Standby Current | 20 A |
| Sensitivity | 2.66 ± 11% FT |
| Battery life (with alkaline battery) | Minimum 1 year |
| Operating Temperature | 0°C to + 60°C |
| Humidity (non-condensing) | 10% to 95% Relative |
| Diamension | 105mm (Dia.) X 40mm (H) |

**NAVEEN
ALARM SYSTEMS
INDIA PVT LTD**

1/10 Gopalakrishna Street,
T. Nagar, Chennai 600 017, India
Ph: 91 44 - 2815 7868
info@naveenalarm.com
www.naveenalarm.com